

ABC POWDER · MAP 40

ABC Dry Powder Fire Extinguisher

2 kg

- ISI marked · IS 15683
- 5-year warranty
- Fire classes: A, B, C and electrical
- MAP 40 · home, shop, small office

A Wood, paper, cloth **B** Oil, petrol, paint **C** LPG, gas  Electrical

TECHNICAL SPECIFICATIONS

GENERAL		PERFORMANCE	
Capacity	2 kg	Throw range	2.5 m (approx.)
Type	Portable, stored pressure	Operating temperature	-30 to +60 °C
Extinguishing agent	ABC dry powder (MAP 40)	BUILD	
Expelling agent	Nitrogen (UHP grade)	Body	Mild steel sheet, max. 0.25% C, 0.05% P and 0.05% S (IS 513)
Fire classes	A, B, C and electrical	Sheet thickness	1.8 mm
Fire rating	1A:21B	Valve	Brass, M30x1.5 male thread
IS standard	IS 15683	Siphon tube	PVC / Plastic
Approvals	BIS (ISI mark)	Finish	PO Red as per IS 5 (Shade 538)
Warranty	5 years	SIZE & WEIGHT	
PERFORMANCE		Height	380 mm (approx.)
Working pressure	15 bar	Diameter	106 ± 5 mm
Max service pressure	18 bar	Weight when full	3.7 kg (approx.)
Test pressure	35 bar	Empty weight	1.4 kg
Burst pressure (body)	55 bar	Carton size	255 x 255 x 420 mm
Discharge time	14 sec (approx.)	IN THE BOX	
Discharge	95% (approx.)	In the box	Wall mounting bracket with screw
		SERVICE	
		Maintenance	IS 2190

How to use: P.A.S.S.

1. **Pull** the safety pin
2. **Aim** at the base of the fire
3. **Squeeze** the handle
4. **Sweep** side to side

Care & service

Check it every month: gauge in the green zone, pin and seal in place, nothing blocking it. Get it serviced as per IS 2190 and refilled after any use. FIRENET does refilling, hydro testing and AMC in Pune & PCMC.