



ABC POWDER · MAP 40

ABC Dry Powder Fire Extinguisher

9 kg

- ISI marked · IS 15683
- 5-year warranty
- Fire classes: A, B, C and electrical
- MAP 40 · factory, godown, parking

A Wood, paper, cloth **B** Oil, petrol, paint **C** LPG, gas  Electrical

TECHNICAL SPECIFICATIONS

GENERAL		PERFORMANCE	
Capacity	9 kg	Operating temperature	-30 to +55 °C
Type	Portable, stored pressure	BUILD	
Extinguishing agent	ABC dry powder (MAP 40)	Body	Mild steel sheet, max. 0.25% C, 0.05% P and 0.05% S
Expelling agent	Nitrogen (UHP grade)	Sheet thickness	2.0 mm
Fire classes	A, B, C and electrical	Valve	Brass
Fire rating	3A	Hose / nozzle	Rubber braided EPDM hose (length 560 mm) with plastic nozzle
IS standard	IS 15683	Siphon tube	Plastic
Approvals	BIS (ISI mark)	Pressure gauge	Yes
Warranty	5 years	Finish	PO Red as per IS 5 (Shade 538)
PERFORMANCE		SIZE & WEIGHT	
Working pressure	15 bar	Height	575 mm
Max service pressure	18 bar	Diameter	180 ± 10 mm
Test pressure	35 bar	Weight when full	14.0 kg (approx.)
Burst pressure (body)	55 bar	Empty weight	4.3 kg
Discharge time	31 sec (approx.)	Carton size	210 × 210 × 630 mm
Discharge	94% (approx.)	IN THE BOX	
Throw range	6 m (approx.)	In the box	Wall bracket with screws (powder-coated mild steel)
		SERVICE	
		Maintenance	IS 2190

How to use: P.A.S.S.

1. **Pull** the safety pin
2. **Aim** at the base of the fire
3. **Squeeze** the handle
4. **Sweep** side to side

Care & service

Check it every month: gauge in the green zone, pin and seal in place, nothing blocking it. Get it serviced as per IS 2190 and refilled after any use. FIRENET does refilling, hydro testing and AMC in Pune & PCMC.