

CLEAN AGENT

## Clean Agent Fire Extinguisher

**4 kg**

- ISI marked · IS 15683:2018
- 5-year warranty
- Fire classes: A, B, C and electrical
- No residue · electronics, offices

**A**

Wood, paper, cloth

**B**

Oil, petrol, paint

**C**

LPG, gas

**Electrical**

### TECHNICAL SPECIFICATIONS

| GENERAL             |                                      | PERFORMANCE           |                                         |
|---------------------|--------------------------------------|-----------------------|-----------------------------------------|
| Capacity            | 4 kg                                 | Throw range           | 2–4 m                                   |
| Type                | Portable, stored pressure (nitrogen) | Operating temperature | –30 to +60 °C                           |
| Extinguishing agent | Clean agent: HFC–227ea / FK–5–1–12   | BUILD                 |                                         |
| Expelling agent     | Nitrogen (stored pressure)           | Body                  | Steel, red epoxy powder coat (RAL 3000) |
| Fire classes        | A, B, C and electrical               | Finish                | Red epoxy powder coat (RAL 3000)        |
| Fire rating         | 2A:34B                               | Other                 | Non-conductive discharge; no residue    |
| IS standard         | IS 15683:2018                        | SIZE & WEIGHT         |                                         |
| Approvals           | BIS (ISI mark)                       | Height                | 490 mm (approx.)                        |
| Warranty            | 5 years                              | Diameter              | 140 ± 5 mm                              |
| PERFORMANCE         |                                      | Weight when full      | 6.5 kg                                  |
| Working pressure    | 15 bar (at 27 °C)                    | Empty weight          | 2.5 kg                                  |
| Test pressure       | 30 bar (hydrostatic)                 | Shipping weight       | 6.9 kg                                  |
| Discharge time      | 9–15 sec                             | IN THE BOX            |                                         |
| Discharge           | 96%                                  | In the box            | Wall bracket                            |
|                     |                                      | SERVICE               |                                         |
|                     |                                      | Maintenance           | IS 2190                                 |

#### How to use: P.A.S.S.

1. **Pull** the safety pin
2. **Aim** at the base of the fire
3. **Squeeze** the handle
4. **Sweep** side to side

#### Care & service

Check it every month: gauge in the green zone, pin and seal in place, nothing blocking it. Get it serviced as per IS 2190 and refilled after any use. FIRENET does refilling, hydro testing and AMC in Pune & PCMC.