



CLEAN AGENT

Clean Agent Fire Extinguisher (SS Body)

1kg

- ISI marked · IS 15683:2018
- 5-year warranty
- Fire classes: A, B, C and electrical
- Stainless steel · data centres, hospitals

A Wood, paper, cloth **B** Oil, petrol, paint **C** LPG, gas  Electrical

TECHNICAL SPECIFICATIONS

GENERAL

Capacity	1 kg
Type	Portable, stored pressure (nitrogen)
Extinguishing agent	Clean agent: HFC-227ea / FK-5-1-12
Expelling agent	Nitrogen (stored pressure)
Fire classes	A, B, C and electrical
IS standard	IS 15683:2018
Approvals	BIS (ISI mark)
Warranty	5 years

PERFORMANCE

Working pressure	15 bar (at 27 °C)
Test pressure	30 bar (hydrostatic)
Discharge time	9-15 sec
Throw range	2-4 m
Operating temperature	-30 to +60 °C

BUILD

Body	AISI 304 / 316 stainless steel, polished
Valve	Forged chrome-plated brass or SS, squeeze grip

SERVICE

Maintenance	IS 2190
-------------	---------

How to use: P.A.S.S.

1. **Pull** the safety pin
2. **Aim** at the base of the fire
3. **Squeeze** the handle
4. **Sweep** side to side

Care & service

Check it every month: gauge in the green zone, pin and seal in place, nothing blocking it. Get it serviced as per IS 2190 and refilled after any use. FIRENET does refilling, hydro testing and AMC in Pune & PCMC.