



CLEAN AGENT

Clean Agent Fire Extinguisher (SS Body)

4 kg

- ISI marked · IS 15683:2018
- 5-year warranty
- Fire classes: A, B, C and electrical
- Stainless steel · data centres, hospitals

A Wood, paper, cloth **B** Oil, petrol, paint **C** LPG, gas  Electrical

TECHNICAL SPECIFICATIONS

GENERAL		PERFORMANCE	
Capacity	4 kg	Throw range	2–4 m
Type	Portable, stored pressure (nitrogen)	Operating temperature	–30 to +60 °C
Extinguishing agent	Clean agent: HFC-227ea / FK-5-1-12	BUILD	
Expelling agent	Nitrogen (stored pressure)	Body	AISI 304 / 316 stainless steel, polished
Fire classes	A, B, C and electrical	Valve	Forged chrome-plated brass or SS, squeeze grip
Fire rating	2A:34B	SIZE & WEIGHT	
IS standard	IS 15683:2018	Height	500 mm (approx.)
Approvals	BIS (ISI mark)	Diameter	140 ± 5 mm
Warranty	5 years	Weight when full	6.5 kg
PERFORMANCE		Empty weight	2.5 kg
Working pressure	15 bar (at 27 °C)	Shipping weight	6.9 kg
Test pressure	30 bar (hydrostatic)	IN THE BOX	
Discharge time	9–15 sec	In the box	Wall bracket
Discharge	96%	SERVICE	
		Maintenance	IS 2190

How to use: P.A.S.S.

1. **Pull** the safety pin
2. **Aim** at the base of the fire
3. **Squeeze** the handle
4. **Sweep** side to side

Care & service

Check it every month: gauge in the green zone, pin and seal in place, nothing blocking it. Get it serviced as per IS 2190 and refilled after any use. FIRENET does refilling, hydro testing and AMC in Pune & PCMC.