



FOAM (AFFF)

Foam Fire Extinguisher

9 L

- ISI marked · IS 15683
- 5-year warranty
- Fire classes: A and B
- Oils, paints, thinners and fuels

A

Wood, paper, cloth

B

Oil, petrol, paint

TECHNICAL SPECIFICATIONS

GENERAL		PERFORMANCE	
Capacity	9 L	Throw range	3–6 m
Type	Portable, stored pressure (dry nitrogen)	Operating temperature	+5 to +60 °C
Extinguishing agent	AFFF foam, 3 % / 6 % solution	BUILD	
Expelling agent	Nitrogen (stored pressure)	Body	Red epoxy powder coat (RAL 3000), polymer lining inside
Fire classes	A and B	Sheet thickness	2.0 mm
Fire rating	4A:144B	Siphon tube	Plastic
IS standard	IS 15683	Pressure gauge	Yes
Approvals	BIS (ISI mark)	Finish	Red epoxy powder coat (RAL 3000)
Warranty	5 years	SIZE & WEIGHT	
PERFORMANCE		Height	575 mm (approx.)
Working pressure	15 bar (at 27 °C)	Diameter	180 ± 10 mm
Max service pressure	17 bar	Weight when full	14.0 kg (approx.)
Test pressure	30 bar (hydrostatic)	Empty weight	4.3 kg
Burst pressure (body)	55 bar	Carton size	210 × 210 × 630 mm
Discharge time	15–30 sec	IN THE BOX	
Discharge	97% (approx.)	In the box	Wall bracket with screws (powder-coated mild steel)
		SERVICE	
		Maintenance	IS 2190

How to use: P.A.S.S.

1. **Pull** the safety pin
2. **Aim** at the base of the fire
3. **Squeeze** the handle
4. **Sweep** side to side

Care & service

Check it every month: gauge in the green zone, pin and seal in place, nothing blocking it. Get it serviced as per IS 2190 and refilled after any use. FIRENET does refilling, hydro testing and AMC in Pune & PCMC.