

KITCHEN (K-TYPE)

Kitchen Fire Extinguisher

6 L

- ISI marked · IS 15683 (K-Class)
- 5-year warranty
- Fire classes: K (cooking oil and fat) and A
- Cooking oil and fat fires

A

Wood, paper, cloth

K

Cooking oil

TECHNICAL SPECIFICATIONS

GENERAL		BUILD	
Capacity	6 L	Sheet thickness	1 mm
Type	Portable, stored pressure	Valve	Brass
Extinguishing agent	Wet chemical	Hose / nozzle	Rubber braided EPDM hose
Expelling agent	Nitrogen (UHP grade)	Siphon tube	SS
Fire classes	K (cooking oil and fat) and A	Pressure gauge	Yes (brass)
Fire rating	25F	Finish	Smooth finish
IS standard	IS 15683 (K-Class)	SIZE & WEIGHT	
Approvals	BIS (ISI mark)	Height	500 mm
Warranty	5 years	Diameter	150 ± 10 mm
PERFORMANCE		Weight when full	8.9 kg
Working pressure	9 bar	Empty weight	2.9 kg
Max service pressure	15 bar	Shipping weight	9.3 kg
Test pressure	35 bar	Carton size	255 x 255 x 420 mm
Burst pressure (body)	55 bar	IN THE BOX	
Discharge time	20 sec	In the box	Wall bracket with screws (powder-coated mild steel)
Discharge	95%	SERVICE	
Operating temperature	+5 to +55 °C	Maintenance	IS 2190

How to use: P.A.S.S.

1. **Pull** the safety pin
2. **Aim** at the base of the fire
3. **Squeeze** the handle
4. **Sweep** side to side

Care & service

Check it every month: gauge in the green zone, pin and seal in place, nothing blocking it. Get it serviced as per IS 2190 and refilled after any use. FIRENET does refilling, hydro testing and AMC in Pune & PCMC.