



KITCHEN (K-TYPE)

Kitchen Fire Extinguisher (K-Type, SS Body)

2 L

- ISI marked · IS 15683 (K-Class)
- 5-year warranty
- Fire classes: K (cooking oil and fat) and A
- Stainless steel · commercial kitchens

A

Wood, paper, cloth

K

Cooking oil

TECHNICAL SPECIFICATIONS

GENERAL		BUILD	
Capacity	2 L	Body	Stainless steel
Type	Portable, stored pressure	Sheet thickness	1 mm
Extinguishing agent	Wet chemical	Valve	Brass
Expelling agent	Nitrogen (UHP grade)	Hose / nozzle	Rubber braided EPDM hose
Fire classes	K (cooking oil and fat) and A	Siphon tube	SS
Fire rating	5F	Pressure gauge	Yes (brass)
IS standard	IS 15683 (K-Class)	Finish	Smooth finish
Approvals	BIS (ISI mark)	SIZE & WEIGHT	
Warranty	5 years	Height	440 mm
PERFORMANCE		Diameter	110 ± 10 mm
Working pressure	9 bar	Weight when full	3.7 kg
Max service pressure	15 bar	Empty weight	1.7 kg
Test pressure	35 bar	Shipping weight	4.0 kg
Burst pressure (body)	55 bar	IN THE BOX	
Discharge time	10 sec	In the box	Wall bracket with screws (powder-coated mild steel)
Discharge	95%	SERVICE	
Operating temperature	+5 to +55 °C	Maintenance	IS 2190

How to use: P.A.S.S.

1. **Pull** the safety pin
2. **Aim** at the base of the fire
3. **Squeeze** the handle
4. **Sweep** side to side

Care & service

Check it every month: gauge in the green zone, pin and seal in place, nothing blocking it. Get it serviced as per IS 2190 and refilled after any use. FIRENET does refilling, hydro testing and AMC in Pune & PCMC.