



AUTOMATIC / MODULAR

Modular Fire Extinguisher (Clean Agent)

15 kg

- 5-year warranty
- Automatic · server and panel rooms

TECHNICAL SPECIFICATIONS

GENERAL		PERFORMANCE	
Capacity	15 kg	Area protected	5–6 m ²
Type	Automatic, ceiling-mounted modular unit	Hanging height	2.5 m
Extinguishing agent	Clean agent	BUILD	
Expelling agent	Nitrogen (UHP grade)	Body	Mild steel sheet, max. 0.25% C, 0.05% P and 0.05% S (IS 513)
Warranty	5 years	Sheet thickness	2 mm
PERFORMANCE		Valve	Forged brass, M30×1.5 male thread, sprinkler type
Working pressure	15 bar	Pressure gauge	Yes
Max service pressure	18 bar	Finish	PO Red as per IS 5 (Shade 538)
Test pressure	35 bar	SIZE & WEIGHT	
Discharge time	15–20 sec (approx.)	Diameter	400 ± 10 mm
Discharge	95%	Empty weight	6.4 kg
Operating temperature	–30 to +60 °C	Shipping weight	22 kg
Volume protected	15 m ³	Carton size	420 × 420 × 330 mm
		IN THE BOX	
		In the box	Ceiling mounting stand

How it works

1. Works on its own: when the heat below reaches the set temperature, the glass bulb bursts and the unit discharges
2. Mount it above the risk it protects, at the height shown in the specifications
3. No one needs to be present

Care & service

Check the gauge (where fitted), mounting and expiry date regularly and keep the area below clear. Replace or recharge the unit after it goes off.