



AUTOMATIC / MODULAR

Modular Fire Extinguisher (Clean Agent)

5 kg

- 5-year warranty
- Automatic · server and panel rooms

TECHNICAL SPECIFICATIONS

GENERAL		PERFORMANCE	
Capacity	5 kg	Hanging height	2 m
Type	Automatic, ceiling-mounted modular unit	BUILD	
Extinguishing agent	Clean agent	Body	Mild steel sheet, max. 0.25% C, 0.05% P and 0.05% S (IS 513)
Expelling agent	Nitrogen (UHP grade)	Sheet thickness	2 mm
Warranty	5 years	Valve	Forged brass, M30x1.5 male thread, sprinkler type
PERFORMANCE		Pressure gauge	Yes
Working pressure	15 bar	Finish	PO Red as per IS 5 (Shade 538)
Max service pressure	18 bar	SIZE & WEIGHT	
Test pressure	35 bar	Diameter	230 ± 10 mm
Discharge time	6–8 sec (approx.)	Weight when full	7.6 kg (approx.)
Discharge	95%	Empty weight	2.6 kg
Operating temperature	–30 to +60 °C	Shipping weight	7.7 kg
Area protected	1.5–2 m ²	Carton size	250 × 250 × 300 mm
		IN THE BOX	
		In the box	Ceiling mounting stand

How it works

1. Works on its own: when the heat below reaches the set temperature, the glass bulb bursts and the unit discharges
2. Mount it above the risk it protects, at the height shown in the specifications
3. No one needs to be present

Care & service

Check the gauge (where fitted), mounting and expiry date regularly and keep the area below clear. Replace or recharge the unit after it goes off.