



AUTOMATIC / MODULAR

Modular Fire Extinguisher (Clean Agent, SS Body)

10 kg

- 5-year warranty
- Automatic · stainless steel

TECHNICAL SPECIFICATIONS

GENERAL		PERFORMANCE	
Capacity	10 kg	Volume protected	10 m ³ (approx.)
Type	Automatic, ceiling-mounted modular unit	Area protected	4–5 m ²
Extinguishing agent	Clean agent	Hanging height	1.75–2.25 m
Expelling agent	Nitrogen (UHP grade)	BUILD	
Warranty	5 years	Body	Stainless steel
PERFORMANCE		SIZE & WEIGHT	
Working pressure	15 bar	Diameter	300 ± 10 mm
Test pressure	35 bar	Weight when full	14.11 kg
Discharge time	10–15 sec (approx.)	Empty weight	4.11 kg
Discharge	95%	Shipping weight	14.5 kg
Operating temperature	–30 to +60 °C	IN THE BOX	
		In the box	Ceiling mounting stand

How it works

1. Works on its own: when the heat below reaches the set temperature, the glass bulb bursts and the unit discharges
2. Mount it above the risk it protects, at the height shown in the specifications
3. No one needs to be present

Care & service

Check the gauge (where fitted), mounting and expiry date regularly and keep the area below clear. Replace or recharge the unit after it goes off.