

WATER & WATER MIST

Water Fire Extinguisher

9 L

- ISI marked · IS 15683
- 5-year warranty
- Fire classes: A
- Wood, paper, cloth, cardboard

A

Wood, paper, cloth



TECHNICAL SPECIFICATIONS

GENERAL		BUILD	
Capacity	9 L	Body	Mild steel sheet, max. 0.25% C, 0.05% P, 0.05% S (IS 513)
Type	Portable, stored pressure	Sheet thickness	2.0 mm (top) / 2.5 (bottom)
Extinguishing agent	Water	Valve	Brass, M30x1.5 male thread
Expelling agent	Nitrogen (UHP grade)	Hose / nozzle	Rubber braided EPDM hose (Burst pressure ≥ 55 bar)
Fire classes	A	Siphon tube	PVC / Plastic
Fire rating	3A	Pressure gauge	Yes
IS standard	IS 15683	Finish	PO Red as per IS 5 (Shade 538)
Approvals	BIS (ISI mark)	SIZE & WEIGHT	
Warranty	5 years	Height	575 mm (approx.)
PERFORMANCE		Diameter	180 ± 5 mm
Working pressure	15 bar	Weight when full	13.9 kg (approx.)
Max service pressure	18 bar	Empty weight	5.0 kg
Test pressure	35 bar	Shipping weight	14.5 kg
Burst pressure (body)	55 bar	Carton size	210 × 210 × 630 mm
Discharge time	35 sec (approx.)	IN THE BOX	
Discharge	97% (approx.)	In the box	Wall mounting bracket with screw
Throw range	4–6 m	SERVICE	
Operating temperature	+5 to +60 °C	Maintenance	IS 2190

How to use: P.A.S.S.

1. **Pull** the safety pin
2. **Aim** at the base of the fire
3. **Squeeze** the handle
4. **Sweep** side to side

Care & service

Check it every month: gauge in the green zone, pin and seal in place, nothing blocking it. Get it serviced as per IS 2190 and refilled after any use. FIRENET does refilling, hydro testing and AMC in Pune & PCMC.